






# HARMAN LUXURY AUDIO

## Table of Contents

<b>Preamplifiers .....</b>	<b>3</b>
<b>Players.....</b>	<b>4</b>
<b>Integrated Amplifiers .....</b>	<b>5</b>
<b>Power Amplifiers .....</b>	<b>6</b>
<b>Headphones.....</b>	<b>7</b>
<b>Terms and Conditions.....</b>	<b>8</b>

# PREAMPLIFIERS

Model Name	Description	Material Number	MSRP
	<p>Dual-monaural Preamplifier with Pure Phono</p> <ul style="list-style-type: none"> <li>• Analog Inputs: 2 balanced (XLR), 3 single-ended (RCA) line, 1 single-ended (RCA) phono w/ ground</li> <li>• Analog Outputs: 1 balanced (XLR); 1 pair single-ended (RCA), 1 headphone (¼", 6.3mm TS)</li> <li>• Output Impedance: &lt;80Ω single ended, &lt;160Ω balanced</li> <li>• Dimensions (H x W x D): Height (with feet): 3.75" / Height (without feet): 3.25" x 17.25" x 18" (10.2cm/8.9cm x 43.8cm x 45.7cm)</li> <li>• Weight: 39 lbs (17.7kg)</li> <li>• Packaged dimensions (H x W x D): 26.7" x 16" x 26.7" (679 x 406 x 679mm)</li> <li>• Packaged weight: 64 lb (28.8 kg)</li> </ul>	<p>NO523EU UPC: 050667370756</p>	<p>22.950 €</p>
	<p>Dual-Monaural Pure Path Preamplifier with Precision Link DAC and Pure Phono</p> <ul style="list-style-type: none"> <li>• Analog Inputs: 2 balanced (XLR), 3 single-ended (RCA) line, 1 single-ended (RCA) phono w/ ground</li> <li>• Digital Inputs: 1 balanced (XLR); 2 coaxial (RCA); 2 optical (Toslink); 1 USB-B asynchronous</li> <li>• Analog Outputs: 1 balanced (XLR); 1 pair single-ended (RCA), 1 headphone (¼", 6.3mm TS)</li> <li>• Output Impedance: &lt;80Ω single ended, &lt;160Ω balanced</li> <li>• Dimensions (H x W x D): Height (with feet): 3.75" / Height (without feet): 3.25" x 17.25" x 18" (10.2cm / 8.9cm x 43.8 cm x 45.7 cm)</li> <li>• Weight: 41 lbs (17.7kg)</li> <li>• Packaged dimensions (H x W x D): 26.5" x 16.3" x 26.5" (673 x 413 x 673mm)</li> <li>• Packaged weight: 63 lb (28.6 kg)</li> </ul>	<p>NO526EU UPC: 050667370794</p>	<p>28.850 €</p>
	<p>Preamplifier with PurePath fully discrete, direct-coupled, dual-monaural line-level class A preamp circuitry</p> <p>Analog input connectors:</p> <ul style="list-style-type: none"> <li>• 2 pairs balanced line-level inputs (XLR)</li> <li>• 2 pairs single-ended line-level inputs (RCA)</li> <li>• 1 pair single-ended moving-coil phono inputs (RCA)</li> <li>• 1 pair single-ended moving-magnet phono inputs (RCA)</li> </ul> <p>Digital audio connectors:</p> <ul style="list-style-type: none"> <li>• 2 coaxial S/PDIF inputs (RCA)</li> <li>• 2 optical S/PDIF inputs (Toslink)</li> <li>• 1 balanced AES/EBU input (XLR)</li> <li>• 1 asynchronous USB input (USB-B)</li> </ul> <p>Output connectors:</p> <ul style="list-style-type: none"> <li>• 1 pair single-ended line-level outputs (RCA)</li> <li>• 1 pair balanced line-level outputs (XLR)</li> </ul> <p>Control connectors:</p> <ul style="list-style-type: none"> <li>• 1 RS-232 port (DB-9)</li> <li>• 1 Ethernet port (RJ-45)</li> <li>• 1 USB port for firmware updates (USB-A)</li> <li>• 1 baseband IR input (¼"/3.5mm phone jack)</li> <li>• 1 programmable 12V DC trigger output, 100mA maximum (¼"/3.5mm phone jack)</li> <li>• 1 programmable 12V DC trigger input (¼"/3.5mm phone jack)</li> </ul> <p>Power consumption:</p> <ul style="list-style-type: none"> <li>• Power on: 70W</li> <li>• Power on, headphones connected: 85W</li> <li>• Normal standby: 65W</li> <li>• Power Save standby: 4W</li> <li>• Green standby: &lt;0.4W</li> </ul> <ul style="list-style-type: none"> <li>• Dimensions (H x W x D): 4.96 x 17.25 x 19.25" (126 x 438 x 489mm)</li> <li>• Packed Dimensions (H x W x D): 13.63 x 24.25 x 29" (346 x 616 x 737mm)</li> <li>• Net Weight: 34 lbs (15.4kg)</li> <li>• Packed Weight: 48 lbs (21.7kg)</li> </ul>	<p>MLNO5206EU UPC: 050667376505</p>	<p>13.100 €</p>

# PLAYERS



No519

**Audio Player**  
 Now featuring ROON and MQA

- Slot loading CD player
- Digital inputs: 1 balanced; 2 coaxial; 2 optical; 1 USB asynchronous, Bluetooth receiver
- Mass storage: 2 USB type A
- Network: Ethernet, Wi-Fi 802.11b/g/n
- PCM input sample rates: 32, 44.1, 48, 88.2, 96, 176.4, and 192kHz
- PCM input bit depth: up to 32
- DSD: native, single (2.8MHz) and double-speed (5.6MHz)
- Main analog outputs: 1 pair balanced; 1 pair single-ended
- Headphone output: 1 1/4-inch (6.3mm)
- Digital outputs: 1 balanced; 1 coaxial; 1 optical
- Control I/O: Ethernet, RS-232, Trigger In and Out, IR In
- Software update: Network, USB
- Power requirements: 100, 115, or 230V AC, factory set for destination country
- Control apps: iOS, Android, web browser
- Dimensions: 17.25" x 16" x 5.75"
- Weight: 36 lbs (16.4kg)
- Packaged dimensions (H x W x D): 26" x 26" x 17" (660 x 660 x 432mm)
- Packaged weight: 56 lb (25.5 kg)

NO519EU  
 UPC: 050667370718

28.850 €



No5101

**Network Streaming CD/SACD Player and DAC**

- 3-in-1 companion source for N°5805 or N°5802
- 1. Slot Loading SACD Player
- 2. Network Streamer
- 3. DAC
- Plays all disc formats, including CD/SACD, CD-A, CD-R and CD-RW
- Supports FLAC, WAV, AIFF, OGG, MP3, AAC and WMA
- USB -A for USB Drive file playback
- Precision Link II DAC

**Technical Specifications:**

- Output voltage: 3.0V RMS single-ended at full scale (0dBFS)
- 6.0V RMS balanced at full scale (0dBFS)
- Total harmonic distortion + noise:
  - <0.004%, 20Hz to 20kHz, single-ended, 3V RMS output (44.1kHz/16 bit signal)
  - <0.003%, 20Hz to 20kHz, balanced, 6V RMS output (44.1kHz/16 bit signal)
  - <0.003%, 20Hz to 20kHz, single-ended, 3V RMS output (192kHz/24 bit signal)
  - <0.002%, 20Hz to 20kHz, balanced, 6V RMS output (192kHz/24 bit signal)
- Signal-to-noise ratio: >94dB single-ended (wideband, unweighted, referred to 3V RMS output)
- >106dB balanced (wideband, unweighted, referred to 6V RMS output)
- Power consumption: Standby: <0.4W
- Power on: 32W

MLNO5101EU  
 UPC: 050667375829

7.750 €



No5105

**Turntable**

- Custom 10-inch tonearm
- Precision roller ball bearings in all directions
- Ultra-precision movement and damping
- Digitally controlled 12V synchronous motor
- Fully digital motor electronics with 33/45 speed selections
- Stable speed and low wow/flutter
- Global power supply
- Massive solid brushed aluminum plinth precision machined from a single billet
- 14lb solid aluminum platter - backside coated with resonance absorbing material
- Adjustable isolated feet
- Glass and aluminum front panel with speed and standby control
- Integrated bubble level

MLNO5105  
 MLNO5105MC

8.750 €

10.250 €

# INTEGRATED AMPLIFIERS



Model Name	Description	Material Number	MSRP
No585.5	<p>Integrated Amplifier with Phono Stage</p> <ul style="list-style-type: none"> <li>• 200Wpc into 8 ohms   350Wpc into 4 ohms</li> <li>• Analog audio inputs: One XLR and three RCA stereo pairs</li> <li>• Phono inputs: One RCA stereo pair (configurable for MC/MM) plus ground terminal</li> <li>• Digital audio inputs: One USB, one AES/EBU, two coaxial and two optical</li> <li>• Analog audio outputs: One RCA stereo pair with selectable 80Hz crossover</li> <li>• Communication and control: Ethernet, USB, RS-232, IR input, and 12V trigger input and output</li> <li>• Remote control: IR system remote</li> <li>• Dimensions: 7.6" x 17.1" x 19.9" (193mm x 434mm x 506mm)</li> <li>• Weight: 74 lb (34kg)</li> <li>• Packaged dimensions (H x W x D): 26.4" x 18.9" x 26.4" (670 x 480 x 670mm)</li> <li>• Packaged weight: 96 lb (43.7 kg)</li> </ul>	<p>MLNO585P5EU</p> <p>UPC: 050667372378</p>	20.900 €
No5805	<p>Integrated Amplifier with Phono Stage</p> <ul style="list-style-type: none"> <li>• 125Wpc into 8 ohms   250Wpc into 4 ohms</li> <li>• Analog audio inputs: One XLR and two RCA stereo pairs</li> <li>• Phono inputs: One RCA stereo pair MC and one RCA stereo pair MM plus ground terminal</li> <li>• Digital audio inputs: One USB, one coaxial, two optical, Bluetooth aptX</li> <li>• MQA full decoding on all digital inputs including asynchronous USB</li> <li>• Analog audio outputs: One RCA stereo pair (variable)</li> <li>• Headphone output: One ¼-inch jack (front panel)</li> <li>• Communication and control: Ethernet, USB, RS-232, IR input, and 12V trigger input and output</li> <li>• Dimensions (H x W x D): 5.72" x 17.25" x 19.98" (145 x 438 x 507mm)</li> <li>• Packaged dimensions (H x W x D): 13" x 24" x 28" (330 x 610 x 711mm)</li> <li>• Packaged weight: 73 lbs (33kg)</li> </ul>	<p>MLNO5805EU</p> <p>UPC: 050667373481</p>	12.250 €
No5802	<p>Integrated Amplifier</p> <ul style="list-style-type: none"> <li>• 125Wpc into 8 ohms   250Wpc into 4 ohms</li> <li>• Analog audio inputs: None</li> <li>• Digital audio inputs: One USB, one AES/EBU, two coaxial, two optical, Bluetooth aptX</li> <li>• MQA full decoding on all digital inputs including asynchronous USB</li> <li>• Analog audio outputs: One RCA stereo pair (variable)</li> <li>• Headphone output: One ¼-inch jack (front panel)</li> <li>• Communication and control: Ethernet, USB, RS-232, IR input, and 12V trigger input and output</li> <li>• Dimensions (H x W x D): 5.72" x 17.25" x 19.98" (145 x 438 x 507mm)</li> <li>• Packaged dimensions (H x W x D): 13" x 24" x 28" (330 x 610 x 711mm)</li> <li>• Packaged weight: 72 lbs. (32.6kg)</li> </ul>	<p>MLNO5802EU</p> <p>UPC: 050667373542</p>	10.900 €

# POWER AMPLIFIERS



No536

**Monaural Amplifier**

- Input connectors: one XLR Balanced, one RCA Unbalanced
- Speaker connectors: two pairs of Hurricane loudspeaker outputs with banana-plug sockets (except on 230 VAC version)
- Control connectors: Ethernet, RS-232, Trigger In, Trigger Out, USB-A, Mini USB
- Rated output power: 400W RMS @ 8 ohms, 800W RMS @ 4 ohms, 20Hz to 20kHz at <0.3% THD, full output from 2.83VRMS
- Frequency response: 10Hz to 20kHz +/- 0.2dB
- Signal-to-noise ratio: >85dB, reference level 2.83 VRMS
- Input impedance: 60 kΩ balanced; 30 kΩ unbalanced
- Voltage gain: 26dB
- Input sensitivity: 2.83 VRMS output at 142mVRMS input
- Power requirements: 100V-, 120V-, 230V-; factory set for destination country, 1500W
- Dimensions (H x W x D): 7.65" x 17.75" x 19.83" (119.4 cm x 45.1 cm x 50.4 cm)
- Weight: 100 lbs (45.4kg)
- Packaged dimensions (H x W x D): 26.6" x 15.4" x 28.3" (675 x 390 x 720mm)
- Packaged weight: 119 lb (54.1 kg)

NO536EU

UPC: 050667370831

22.250 €



No534

**Dual-Monaural Amplifier**

- Input connectors: one pair Balanced, one pair single-ended
- Speaker Connectors: four pairs of Hurricane loudspeaker outputs, banana-plug sockets per channel, except on European versions
- Control I/O: Ethernet, RS-232, Trigger In and Out, USB-A, MiniUSB
- Rated Output Power: 250 wpc RMS @ 8Ω, 20Hz to 20kHz @ <0.3% THD, full output from 2.83VRMS
- Frequency Response: 10Hz to 20kHz ±0.2dB
- Signal-to-Noise Ratio: >85dB, reference level: 2.83 VRMS
- Input Impedance: 60 kΩ balanced; 30 kΩ unbalanced
- Voltage Gain: 26dB
- Input Sensitivity: 2.83VRMS output at 142mVRMS input
- Power Requirements: 100V-, 120V-, 230V-, factory set for destination country, 1500W
- Dimensions (H x W x D): (with feet): 7.75" (19.7cm) / (without feet): 7" x 17.75" x 20" (19.7cm/17.8cm x 45.1cm x 50.8cm)
- Weight: 107 lbs (48.5kg)
- Packaged dimensions (H x W x D): 0.7" x 17.8" x 7.8" (17.8 x 451 x 197mm)
- Packaged weight: 124 lb (56.3 kg)

NO534EU

UPC: 050667370671

28.850 €



No5302

**Fully discrete, direct-coupled, dual monaural class AB amplifier**

- Input connectors: 1 pair balanced line-level inputs (XLR)
- 1 pair single-ended line-level inputs (RCA)
- Output connectors: 2 pairs high current multi-way binding posts on all units.
- Control connectors: 1 RS-232 port (DB-9)
- 1 Ethernet port (RJ-45)
- 1 USB port for firmware updates (USB-A)
- 1 baseband IR input (1/8"/3.5mm phone jack)
- 1 programmable 12V DC trigger output, 100mA maximum (1/8"/3.5mm phone jack)
- 1 programmable 12V DC trigger input (1/8"/3.5mm phone jack)
- Power consumption: Maximum: 1000W
- On, idle (stereo mode): 90W
- On, idle (bridged mode): 70W
- Normal standby: 35W
- Power Save standby: 2W
- Green standby: <0.4W
- Dimensions (H x W x D): 5.72 x 17.25 x 20.75" (145 x 438 x 527mm)
- Packed Dimensions (H x W x D): 13.63 x 24.25 x 29" (346 x 616 x 737mm)
- Net Weight: 70 lbs (31.7kg)
- Packed Weight: 85 lbs (38.5kg)

MLNO5302EU  
UPC: 050667376543

12.900 €

# HEADPHONES

Model Name	Description	Material Number	MSRP
No5909	<p>Premium High-Resolution Wireless Adaptive ANC Noise Cancelling Headphone</p> <ul style="list-style-type: none"> <li>• Hi-Res Audio certified: LDAC audio codec</li> <li>Digital circuitry compatible with 24-bit/96kHz processing</li> <li>Acoustic response up to 40kHz</li> <li>• Expertly tuned 40 mm Beryllium coated drivers acoustically optimized to the HARMAN Curve</li> <li>• Bluetooth 5.1 with LDAC, AAC and aptX™ Adaptive technologies</li> <li>• Adaptive Active Noise Cancellation (ANC) with three modes</li> <li>• Ambient Aware mode for situational awareness while on the go</li> <li>• Four-microphone voice array with Smart Wind Adaption</li> <li>• Available colors include Pearl Black, Ice Pewter, Radiant Red</li> </ul> <p><b>Materials</b></p> <ul style="list-style-type: none"> <li>• Premium leather headband and replaceable leather ear cushions</li> <li>• Anodized aluminum frame</li> <li>• Automotive-grade metallic painted ear cups</li> </ul> <p><b>Battery</b></p> <ul style="list-style-type: none"> <li>• Up to 34 hours battery life; 30 hours playtime with ANC enabled</li> <li>• Up to 6 hours playtime with 15-minute quick charge</li> </ul> <p><b>What's Included</b></p> <ul style="list-style-type: none"> <li>• Hard shell carrying case</li> <li>• Cables (audio): <ul style="list-style-type: none"> <li>4 m USB-C to 3.5 mm audio cable</li> <li>1.25 m USB-C to 3.5 mm audio cable</li> </ul> </li> <li>• Cables (power): <ul style="list-style-type: none"> <li>1.25 m USB-C charging cable</li> </ul> </li> <li>• Adapters: <ul style="list-style-type: none"> <li>USB-C to USB-A adaptor</li> <li>3.5 mm to 6.3 mm audio adaptor</li> <li>Airplane audio adaptor</li> </ul> </li> <li>• Microfiber polishing cloth</li> </ul> <p><b>Control</b></p> <ul style="list-style-type: none"> <li>• iOS and Android app control</li> </ul>	<p>MLNO5909BLK</p> <p>MLNO5909GRY</p> <p>MLNO5909RED</p>	<p>980 €</p>

## Terms and Conditions of Sale

THIS PRICE LIST CANCELS ALL PREVIOUS LISTS AND IS VALID UNTIL FURTHER NOTICE.

ALL PRICES, SPECIFICATIONS, APPEARANCE, and TERMS AND CONDITIONS OF SALE ARE SUBJECT TO CHANGE WITHOUT NOTICE.

PRICES EFFECTIVE **June 2024**



HARMAN Luxury Audio Group  
The West Wing, Stirling House,  
Waterbeach,  
Cambridge.  
CB25 9PB  
Phone: +44 (0)1223 203200  
Orders: [luxurysales@harman.com](mailto:luxurysales@harman.com)  
Technical Support: [csupport@harman.com](mailto:csupport@harman.com)

[www.arcam.co.uk](http://www.arcam.co.uk)

© 2022 HARMAN International Industries, Incorporated. All rights reserved.