



HARMAN LUXURY AUDIO

RETAIL PRICE LIST

Table of Contents

PerformaBe.....	3
Performa3	5
Concerta2.....	6
Extreme Climate Loudspeakers	8
Terms and Conditions.....	9



Model Name	Description	Material Number	MSRP
F328Be	<p>3-way Floorstanding Loudspeaker</p> <ul style="list-style-type: none"> • Three 8" Deep Ceramic Composite (DCC) aluminum cone woofers with cast frames • 5.25" DCC aluminum cone midrange with cast frame • 1" Beryllium dome tweeter with acoustic lens waveguide • Recommended amplifier power: 50 - 400 Watts • Nominal impedance: 8 ohms • Loudspeaker Sensitivity (2.83 V/1m): 91dB • Frequency Response: 26Hz - 40kHz (-6dB) • Crossover frequencies: 240Hz, 2.1kHz • Dimensions (H x W x D): 50.9 x 13.5 x 17.6" (1294 x 341.3 x 448.5mm) • Weight: 90 lbs 	<p>REVF328BEBLK (black gloss) UPC: 050667374617</p> <p>REVF328BEWHT (white gloss) UPC: 050667374624</p> <p>REVF328BEWAL (walnut) UPC: 050667374631</p> <p>REVF328BESIL (silver) UPC: 050667374648</p>	22.950 €
F228Be	<p>3-way Floorstanding Loudspeaker</p> <ul style="list-style-type: none"> • Dual 8" (200mm) Deep Ceramic Composite (DCC) aluminum cone woofers with cast frames • 5.25" (130mm) DCC aluminum cone midrange with cast frame • 1" Beryllium dome tweeter with acoustic lens waveguide • Recommended Amplifier Power: 50 – 350 Watts • Nominal Impedance: 8 ohms • Loudspeaker Sensitivity (2.83 V/1m): 90dB • Frequency Response: 33Hz - 40kHz (-6dB) • Crossover Frequency: 260Hz; 2.1kHz • Dimensions (H x W x D): 46.5 x 11.8 x 13.2" (1181 x 302 x 335mm) • Weight: 82 lbs (37.2kg) • Packaged dimensions (H x W x D): 52.8 x 19.5 x 23.7" (1340 x 495 x 603mm) • Packaged weight: 112 lbs (50.9 kg) • Inputs: Dual gold-plated binding posts with shorting straps 	<p>REVF228BEBLK (black gloss) UPC: 050667372002</p> <p>REVF228BEWHT (white gloss) UPC: 050667372019</p> <p>REVF228BEWAL (walnut) UPC: 050667372026</p> <p>REVF228BESIL (silver) UPC: 050667372033</p>	13.150 €
F226Be	<p>3-way Dual 6.5" Floorstanding Loudspeaker</p> <ul style="list-style-type: none"> • Two 6.5" (165mm) Deep Ceramic Composite aluminum cone with cast frame woofers • 5.25" (130mm) Deep Ceramic Composite aluminum cone midrange • 1" (25mm) Beryllium dome tweeter • Recommended Amplifier Power: 50-200 Watts • Frequency Response: 44Hz - 40kHz (-6dB) • Nominal Impedance: 8 ohms • Loudspeaker Sensitivity (2.83V/1m): 90dB • Crossover Frequencies: 260Hz; 2.1kHz • Dimensions (H x W x D): 41.3" x 9.8" x 13.7" (1050mm x 249mm x 347mm) • Weight: 58.8 lbs (26.8kg) 	<p>REVF226BEBLK (black gloss) UPC: 050667374051</p> <p>REVF226BEWHT (white gloss) UPC: 050667374068</p> <p>REVF226BEWAL (walnut) UPC: 050667374075</p> <p>REVF226BESIL (silver) UPC: 050667374082</p>	10.420 €

PERFORMA **Be**⁴™ **LOUDSPEAKER SERIES**



Model Name	Description	Material Number	MSRP
M126Be	<p>2-way Bookshelf Loudspeaker</p> <ul style="list-style-type: none"> • 6.5" (165mm) Deep Ceramic Composite (DCC) aluminum cone woofer with cast frame • 1" (25mm) Beryllium dome tweeter with acoustic lens waveguide • Recommended Amplifier Power: 50 – 150 Watts • Nominal Impedance: 8 ohms • Loudspeaker Sensitivity (2.83 V/1m): 86dB • Frequency Response: 46Hz - 40kHz (-6dB) • Crossover Frequency: 1.7kHz • Dimensions (H x W x D): 15.2 x 8.3 x 10.3" (386 x 211 x 262mm) • Weight: 22 lbs (9.97kg) • Packaged dimensions (H x W x D): 19 x 12.3 x 16.3" (483 x 311 x 413mm) • Packaged weight: 26 lbs (11.6 kg) • Inputs: Gold-plated binding posts 	<p>REVM126BEBLK (black gloss) UPC: 050667371968</p> <p>REVM126BEWHT (white gloss) UPC: 050667371975</p> <p>REVM126BEWAL (walnut) UPC: 050667371982</p> <p>REVM126BESIL (silver) UPC: 050667371999</p>	5.630 €

PERFORMA³ LOUDSPEAKER SERIES



Model Name	Description	Material Number	MSRP
F206	<p>3-Way Floorstanding Tower Loudspeaker</p> <ul style="list-style-type: none"> • Dual 6.5" (16.5 cm) Aluminum Cone, Cast- frame Woofers • 5.25" (13.3 cm) Aluminum Cone, Cast- frame Midrange • 1" (2.5 cm) Aluminum Tweeter with Acoustic Lens Waveguide • Recommended amplifier power range: 50 – 200 watts • Low-frequency extension: 30Hz (–10dB); 34Hz (–6dB); 42Hz (–3dB) • Nominal impedance: 8 ohms • Sensitivity (2.83V/1m): 88dB • Enclosure type: Bass-reflex via front-mounted port • Inputs: Gold-plated binding posts • Dimensions (H x W x D): 41.4" x 9.8" x 13.7" (105.1 cm x 24.9 cm x 34.7 cm) • Weight: 58 lb (26 kg) / Packaged weight: 65 lb (29.4 kg) • Packaged dimensions (H x W x D): 45.3" x 14.2" x 21.1" (115 cm x 45 cm x 53.5 cm) • Piano Black, Piano White, or High Gloss Walnut 	<p>F206 BK (Piano Black) UPC: 848592000080</p> <p>F206 WA (Walnut) UPC: 848592000103</p> <p>F206 WH (White) UPC: 848592000073</p>	4.590 €
M106	<p>2-Way Bookshelf Monitor Loudspeaker</p> <ul style="list-style-type: none"> • 6.5" (16.5 cm) Aluminum Cone, Cast-frame Woofer • 1" (2.5 cm) Aluminum Tweeter with Acoustic Lens Waveguide • Recommended amplifier power range: 50 – 150 watts • Low-frequency extension: 39Hz (–10dB); 54Hz (–6dB); 59Hz (–3dB) • Nominal impedance: 8 ohms • Sensitivity (2.83V/1m): 87dB • Enclosure type: Bass-reflex via rear-mounted port • Inputs: Gold-plated binding posts • Dimensions (H x W x D): 15" x 8.3" x 11" (38.1 cm x 21 cm x 27.8 cm) • Weight: 19 lb (8 kg) / Packaged weight: 22 lb (9.8 kg) • Packaged dimensions (H x W x D): 18.9" x 12.2" x 16.1" (48 cm x 31 cm x 41 cm) • Piano Black or High Gloss Walnut 	<p>M106 BK (Piano Black) UPC: 848592000042</p> <p>M106 WA (Walnut) UPC: 848592000066</p>	2.920 €
M Stand	<p>Optional Floor Pedestal for M105/M106</p> <ul style="list-style-type: none"> • Packed and sold in pairs • Dimensions (H x W x D): 25" x 9.4" x 11.5" (63.5 cm x 23.8 cm x 29.1 cm) • Weight: 8 lb (4 kg) / Packaged weight: 22 lb (10.1 kg) • Packaged dimensions (H x W x D): 27.2" x 13" x 15.6" (69 cm x 33 cm x 39.5 cm) • Black or White Finish 	<p>M STAND BK (Piano Black) UPC: 848592000257</p> <p>M STAND WH (White) UPC: 848592000455</p>	625 €

CONCERTA²™ LOUDSPEAKER SERIES

REVEL[®]



Model Name	Description	Material Number	MSRP
F36	<p>2½-Way Triple 5.25" Floorstanding Loudspeaker</p> <ul style="list-style-type: none"> • HF Drive Component: 1" Aluminum Tweeter with Acoustic Lens Waveguide • LF/MF Drive Component: 3 x 5.25" Aluminum Cone Woofers • Crossover Frequency: 575Hz, 1.8kHz • Input Connections: Five-way binding posts • Sensitivity (2.83V @ 1M): 90dB • Nominal Impedance: 6 Ohms • Recommended Amplifier Power: 30-180W • Dimension(H x W x D): 40.25" x 8.42" x 12.2" • Weight: 41 lbs • Packaged dimensions (H x W x D): 13.2" x 45.5" x 17.7" (335 x 1155 x 450mm) • Packaged weight: 52 lb (23.6 kg) 	<p>F36BK (Black Gloss)</p> <p>F36WH (White Gloss)</p>	2.820 €
F35	<p>2½-Way Triple 5.25" Floorstanding Loudspeaker</p> <ul style="list-style-type: none"> • HF Drive Component: 1" Aluminum Tweeter with Acoustic Lens Waveguide • LF/MF Drive Component: 3 x 5.25" Aluminum Cone Woofers • Crossover Frequency: 575Hz, 1.8kHz • Input Connections: Five-way binding posts • Sensitivity (2.83V @ 1M): 90dB • Nominal Impedance: 6 Ohms • Recommended Amplifier Power: 30-180W • Dimension(H x W x D): 40.25" x 8.42" x 12.2" • Weight: 41 lbs • Packaged dimensions (H x W x D): 13.2" x 45.5" x 17.7" (335 x 1155 x 450mm) • Packaged weight: 52 lb (23.6 kg) 	<p>F35BK (Black Gloss)</p> <p>F35WH (White Gloss)</p>	2.600 €
M16	<p>2-Way 6.5" Bookshelf Loudspeaker</p> <ul style="list-style-type: none"> • HF Drive Component: 1" Aluminum Tweeter with Acoustic Lens Waveguide • LF/MF Drive Component: 6.5" Aluminum Cone Woofer • Crossover Frequency: 2.1kHz • Input Connections: Five-way binding posts • Sensitivity (2.83V @ 1M): 86dB • Nominal impedance: 6 Ohms • Recommended Amplifier Power: 50-120W • Dimension(H x W x D): 14.75" x 8.6" x 10.75" • Weight: 16 lbs • Packaged dimensions (H x W x D): 12.4" x 19.3" x 15.4" (315 x 490 x 390mm) • Packaged weight: 20 lb (9.2 kg) 	<p>M16BK (Black Gloss)</p> <p>M16WH (White Gloss)</p>	1.460 €
M16 Stand	<p>Optional Floor Pedestal for M16</p> <ul style="list-style-type: none"> • Dimensions (H x W x D): 25.5" x 9.37" x 11.4" • Weight: 37 lbs / Packaged weight: 40 lb (18 kg) • Packaged dimensions (H x W x D): 12.8" x 5" x 24.4" (324 x 127 x 620mm) • Black Finish • Packed and sold in pairs 	M16STAND	390 €

LANDSCAPE SPEAKERS

Extreme Climate Loudspeakers (cont.)



Model Name	Description	Material Number	MSRP
L41XC	2-way 4" Landscape Satellite <ul style="list-style-type: none"> • 4" Micro Ceramic Composite Aluminum Cone Woofer • 0.75" Micro Ceramic Composite Aluminum Dome Tweeter • Recommended amplifier power: 60W Max • 70V transformer taps: 7.5W, 15W, 30W, 60W • Voltage: 70V • Rated impedance: 4 Ohm in bypass mode • Sensitivity: 83dB (2.83V @ 1M) in bypass mode • Frequency response: 100Hz-20kHz @ -3dB • Crossover frequency: 5.5kHz • Dimensions (L x W x H): 9.2" (23.2cm) x 6.5" (16.4cm) x 11.3" (28.5cm) • Weight: 9.9 lb (4.5kg) 	REVL41XC	950 €
L42XC	2-way Dual 4" Landscape Bollard <ul style="list-style-type: none"> • Two 4" Micro Ceramic Composite Aluminum Cone Woofer • 1" Micro Ceramic Composite Aluminum Dome Tweeter • Recommended amplifier power: 60W Max • 70V transformer taps: 7.5W, 15W, 30W, 60W • Voltage: 70V • Rated impedance: 4 Ohm in bypass mode • Sensitivity: 86dB (2.83V @ 1M) in bypass mode • Frequency response: 80Hz-20kHz @ -3dB • Crossover frequency: 2.9kHz • Dimensions (L x W x H): 8.58" (21.8cm) x 8.58" (21.8 cm) x 33.7" (85.5cm) • Weight: 20.7 lb (9.4kg) 	REVL42XC	1.600 €
L42MXC	Optional mounting bracket for L42XC	REVL42MXC	120 €
L12XC	12" Landscape Burial Subwoofer <ul style="list-style-type: none"> • 12" Anodized Aluminum Cone Subwoofer • Recommended amplifier power: 250W Max • 70V transformertaps: 31.75W, 62.5W, 125W, 250W • Voltage: 70V • Rated impedance: 8 Ohm without transformer • Sensitivity: 86dB (2.83V @ 1M) without transformer • Frequency response: 25Hz-100Hz @ -3dB • Dimensions (L x W x H): 35" (88.7cm) x 18" (45.5cm) x 34.6" (87.8cm) • Weight: 66.4 lb (30.1kg) Speaker and port assembly; 8.2 lb (3.7kg) rock transformer 	REVL12XC	3.900 €

Terms and Conditions of Sale

THIS PRICE LIST CANCELS ALL PREVIOUS LISTS AND IS VALID UNTIL FURTHER NOTICE.

ALL PRICES, SPECIFICATIONS, APPEARANCE, and TERMS AND CONDITIONS OF SALE ARE SUBJECT TO CHANGE WITHOUT NOTICE.

PRICES EFFECTIVE January 2023



HARMAN Luxury Audio Group
The West Wing, Stirling House,
Waterbeach, Cambridge.
CB25 9PB
Phone: +44 (0)1223 203200
Orders: luxurysales@harman.com
Technical Support: csupport@harman.com

www.revelspeakers.com

© 2022 HARMAN International Industries, Incorporated. All rights reserved.

Revel and the Revel logo are trademarks of HARMAN International Industries, Incorporated, registered in the United States and/ or other countries.
HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC. SACD is a trademark of Sony Corporation. VXP is a registered trademark of Sigma Designs, Inc., in the United States and/or other countries. All rights reserved.